BOLLARD SHOP

Product Data Sheet

IN-GROUND BOLLARDS

114-IG-2000-Y

114mm x 2000mm Inground Bollard

A 114 mm safety yellow steel bollard set in a concrete footing for permanent protection of buildings, equipment and people in car parks, loading docks and warehouses.

114 mm	2000 mm	3.9 mm	2
Diameter	Total length	Wall thickness	Hold-down lugs

SPECIFICATIONS

Code	**114-IG-2000-Y**
Material	**Galvanised steel**
Finish	**Hot dip galvanised, then powder coated**
Colour	**Safety yellow**
Diameter	**114 mm**
Height	**2000 mm**
Wall thickness	**3.9 mm**
Anchoring	**Two 25 mm hold-down lugs**
Set in	**Concrete footing or structural epoxy**
Warranty	**2 year manufacturer warranty**

DRAWINGS



Full length (mm)



Cross-section (mm)

Set in a concrete footing or structural epoxy. Footing size depends on your site. Step-by-step in-ground installation guide (PDF). Drawings not to scale.

2 YEAR WARRANTY



Key features

- Galvanised against rust
- Fade-resistant safety yellow powder coat
- 3.9 mm wall thickness
- Two 25 mm hold-down lugs
- Set in concrete or structural epoxy

Other sizes in safety yellow

90 mm	1500	
114 mm	1800	**2000**
120 mm	1420	
140 mm	1800	2000
165 mm	1800	2000
219 mm	1800	2000

Heights in mm. Some sizes also come with a 5 mm wall.

Scan for price, stock and online ordering

Talk to our team:

Call 1300 766 003

Request a quote